



Cole Metal Products Ltd

'Where Customers and Quality Count'

71 Strand Road, Bootle, Merseyside L20 4BB TEL: 0044 (0)151 933 8588 Email: sales@colemetal.co.uk



THERMIC LANCE SPECIFICATIONS

CODE	DESCRIPTION	COUPLING	LANCE WEIGHT	OUTER DIAM. mm	TUBE WALL mm	WIRE DIAMETER
3L.203.SS315V	20mm NB x 3m SCREWED&SOCKETED LANCE	3/4" BSPT	9.80 Kgs	26.2-27.2	2.6	3.15
3L.153.SS264V	15mm NB x 3m SCREWED&SOCKETED LANCE	1/2" BSPT	7.05 Kgs	21.1-21.7	2.6	2.64
3L.103.SP264V	10mm NB x 3m SCREWED ONE END LANCE	3/8" BSPT	4.22 Kgs	16.8-17.4	2.3	2.64
3L.103.SS264V	10mm NB x 3m SCREWED&SOCKETED LANCE	3/8" BSPT	4.25 Kgs	16.8-17.4	2.3	2.64
3L.163.PP264EWN	16mm x 3m OD PLAIN ENDED LANCE	N/A *	3.86 Kgs	16	2	2.64
3L.123.PP264EWN	12mm x 3m OD PLAIN ENDED LANCE	N/A *	2.38 Kgs	12	2	2.64
** 3L.83.SS	8mm NB SCREWED&SOCKETED THERMIC LANCE	1/4" BSPT	3.9 Kgs	13.3-13.9	2.3	2.64

N.B. ALL THERMIC CUTTING LANCES ARE 3 METRES IN LENGTH AS STANDARD, HOWEVER ANY SIZE UP TO 3 METRE CAN BE MANUFACTURED

** Also in 1 metre lengths as a Stock Item

OXY LANCE SPECIFICATIONS

CODE	DESCRIPTION	COUPLING	LANCE WEIGHT	OUTER DIAM. mm	TUBE WALL mm	WIRE DIAMETER
			3Metre/6Metre			
3L.206.SS	20mm NB SCREWED&SOCKETED OXY-LANCE	3/4" BSPT	4.71/9.42 Kgs	26.2-27.2	2.6	N/A
3L.156.SS	15mm NB SCREWED&SOCKETED OXY-LANCE	1/2" BSPT	3.66/7.32 Kgs	21.7 - 21.1	2.6	N/A
3L.103.SS	10mm NB SCREWED & SOCKETED OXY-LANCE	3/8" BSPT	2.42/4.8 Kgs	16.8-17.4	2.3	N/A
3L.865.SS	8mm NB SCREWED&SOCKETED OXY-LANCE	1/4" BSPT	1.99/3.9 Kgs	13.3-13.9	2.3	N/A

N.B. OXY-LANCES ARE AVAILBLE IN 3 METRE AND 6 METRE LENGTHS

Terminology

NB	Nominal Bore
OD	Outer Diameter
BSPT	British Standard Pipe Thread
N/A*	For use with Compression Holder - no thread required

